

Name:	Manrose	Manrose	Manrose	Manrose
Model ID (Stock Ref.) :	XF120LV	XF120ALV	WF120LV	WF120ALV
SEC Class	F	F	F	F
SEC Value ('Average')	-4.47	-4.47	-4.47	-4.47
SEC Value ('Warm')	3.18	3.18	3.18	3.18
SEC Value ('Cold')	-17.83	-17.83	-17.83	-17.83
Label Required? (Yes/No=Out of scope)	No	No	No	No
Declared as: RVU or NRUVU/UVU or BVU	RVU-UVU	RVU-UVU	RVU-UVU	RVU-UVU
Speed Drive	Variable Speed	Variable Speed	Variable Speed	Variable Speed
Type HRS (Re recuperative, Regenerative, None)	None	None	None	None
Thermal Eff. : (%), NA(if none)	N/A	N/A	N/A	N/A
Max. Flow Rate (m3/h)	129.60	129.60	129.60	129.60
Max. Power Input (W): (@Max.Flow Rate)	25.00	25.00	25.00	25.00
LWA: Sound Power Level (dB)	20.53	20.53	20.53	20.53
Ref. Flow Rate (m3/s)	0.03	0.03	0.03	0.03
Ref. Pressure Diff. (Pa)	TBC	TBC	TBC	TBC
SPL [W]/(m3/h)	0.28	0.28	0.28	0.28
Control Factor & Control Typology: (CTRL/ Typology)				
Control Factor: CTRL	1.00	1.00	1.00	1.00
Control Typology	Manual Control	Manual Control	Manual Control	Manual Control
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	TBC	TBC	TBC	TBC
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;	N/A	N/A	N/A	N/A
Filter Warning (RVU)	No	No	No	No
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)	TBC	TBC	TBC	TBC
Internet Address (for Disassembly Instructions)	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Air Tightness-ID/OD-(m3/h) (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Annual Electricity Consumption: AEC (kWh/a)	9.49	9.49	9.49	9.49
Annual Heating Saved: AHS (kWh/a)				
AHS: Average	13.97	13.97	13.97	13.97
AHS: Warm	6.32	6.32	6.32	6.32
AHS: Cold	27.32	27.32	27.32	27.32