

Name:	Manrose	Manrose	Manrose	Manrose
Model ID (Stock Ref.) :	SF150A	SF150AT	ID150A	ID150AT
SEC Class	C	C	C	C
SEC Value ('Average')	-25.67	-25.67	-25.67	-25.67
SEC Value ('Warm')	-10.17	-10.17	-10.17	-10.17
SEC Value ('Cold')	-52.74	-52.74	-52.74	-52.74
Label Required? (Yes/No=Out of scope)	No	No	No	No
Declared as: RVU or NRUV/UVU or BVU	RVU-UVU	RVU-UVU	RVU-UVU	RVU-UVU
Speed Drive	Multi-Speed	Multi-Speed	Multi-Speed	Multi-Speed
Type HRS (Re recuperative, Regenerative, None)	None	None	None	None
Thermal Eff. : (%), NA(if none)	N/A	N/A	N/A	N/A
Max. Flow Rate (m3/h)	223.20	223.20	223.20	223.20
Max. Power Input (W): (@Max.Flow Rate)	25.00	25.00	25.00	25.00
LWA: Sound Power Level (dB)	N/A - (Ducted)	N/A - (Ducted)	N/A - (Ducted)	N/A - (Ducted)
Ref. Flow Rate (m3/s)	156.24	156.24	156.24	156.24
Ref. Pressure Diff. (Pa)	TBC	TBC	TBC	TBC
SPL [W]/(m3/h)	0.16	0.16	0.16	0.16
Control Factor & Control Typology: (CTRL/ Typology)				
Control Factor: CTRL	0.65	0.65	0.65	0.65
Control Typology	Local Demand Control	Local Demand Control	Local Demand Control	Local Demand Control
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	TBC	TBC	TBC	TBC
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;	N/A	N/A	N/A	N/A
Filter Warning (RVU)	No	No	No	No
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)	TBC	TBC	TBC	TBC
Internet Address (for Disassembly Instructions)	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Air Tightness-ID/DD-(m3/h) (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Annual Electricity Consumption: AEC (kWh/a)	2.63	2.63	2.63	2.63
Annual Heating Saved: AHS (kWh/a)				
AHS: Average	28.30	28.30	28.30	28.30
AHS: Warm	12.80	12.80	12.80	12.80
AHS: Cold	55.36	55.36	55.36	55.36