

Name:	Manrose
Model ID (Stock Ref.) :	CRCHTP
SEC Class	F
SEC Value ('Average')	-9.59
SEC Value ('Warm')	-1.94
SEC Value ('Cold')	-22.95
Label Required? (Yes/No=Out of scope)	No
Declared as: RVU or NRUV/UVU or BVU	RVU-UVU
Speed Drive	Multi-Speed
Type HRS (Regenerative, Regenerative, None)	None
Thermal Eff. : (%), NA(if none)	N/A
Max. Flow Rate (m3/h)	90.00
Max. Power Input (W): (@Max.Flow Rate)	8.00
LWA: Sound Power Level (dB)	56.53
Ref. Flow Rate (m3/s)	63.00
Ref. Pressure Diff. (Pa)	TBC
SPL [W]/(m3/h)	0.13
Control Factor & Control Typology: (CTRL/ Typology)	
Control Factor: CTRL	1.00
Control Typology	Manual Control
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	TBC
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;	N/A
Filter Warning (RVU)	No
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)	TBC
Internet Address (for Disassembly Instructions)	www.manrose.co.uk
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted Vus)	TBC
Air Tightness-ID/DD-(m3/h) (for Non-Ducted Vus)	TBC
Annual Electricity Consumption: AEC (kWh/a)	4.37
Annual Heating Saved: AHS (kWh/a)	
AHS: Average	13.97
AHS: Warm	6.32
AHS: Cold	27.32