

4" Axial Fan Range (SFP down to 0.42)

Designed for wall or ceiling mounting, this comprehensive range offers a wide selection of quiet and efficient models for use in bathrooms and toilets. Comes complete with a backdraught shutter.

Cat No.	Product Type
LXF100S	Standard model for remote switching
LXF100P	As above supplied with pullcord switch
LXF100T	Timer model incorporating integral adjustable electronic timer (1-20 mins)
LXF100H	Humidity control which is adjustable between 40% RH and 95% RH complete with integral adjustable timer (1-20 mins)
LXF100PIR	PIR activated model which switches on as a person enters the room and runs on after the room is vacated. There is no need to connect to a separate switch timer adjustable between 1-20mins. Requires no switched live.

Additional Information

Maximum Pressure:	Fan Speed:	Sound Volume :	Maximum Operating Temperature:	Maximum Airflow l/s:	Power Consumption (Watts):
20 p.a.	2400 r.p.m.	41 dB(A)	40°C	25.5	10.77

6" Axial Fan Range (SFP down to 0.28)

Designed for wall or ceiling mounting, the Efficient and easy to install range offers an alternative style and design to the traditional 6" Kitchen style. Comes complete with a backdraught shutter.



Cat No.	Product Type
LXF150BT	Timer model incorporating integral adjustable electronic timer (1-20 mins)
LXF150BH	Humidity control which is adjustable between 40% RH and 95% RH complete with integral adjustable timer (1-20 mins)
LXF150BPIR	PIR activated model which switches on as a person enters the room and runs on after the room is vacated. There is no need to connect to a separate switch timer adjustable between 1-20mins. Requires no switched live.

Additional Information

Maximum Pressure:	Fan Speed:	Sound Volume :	Maximum Operating Temperature:	Maximum Airflow l/s:	Power Consumption (Watts):
50 p.a.	2400 r.p.m.	40 dB(A)	40°C	64	18