

# Electrical Controllers

## ELECTRICAL ACCESSORIES



1346



MANHR1345



1351



1361



1362

## Technical Details

The Manrose range of electrical accessories are designed to upgrade the switching mechanism of any standard fan providing that the electrical load is not less than 20 Watts or more than 200 Watts. A complete range of options are available in these remote control wall-mounted units.

### Fan Isolating Switch

3 pole, 1 gang fan isolating switch.

| Cat. No. | Description          |
|----------|----------------------|
| 1346     | Fan isolating switch |

### Boost Speed Switch

For the Manrose range of heat recovery units.

| Cat. No.  | Description        |
|-----------|--------------------|
| MANHR1345 | Boost speed switch |

### Timer Model

Incorporating an electronic time delay switch which allows the fan to run on after the room has been vacated and is easily adjustable between 1-20 mins. Fits single pattress 20mm deep.

| Cat. No. | Description          |
|----------|----------------------|
| 1351     | Remote timer control |

### Humidistat Models

Designed to operate the fan when the relative humidity reaches a pre-set level. This unit is adjustable between 20-90% RH and comes complete with an on/off switch which fits a double pattress. Also available with adjustable timer. Fits single pattress 20mm deep.

| Cat. No. | Description   |
|----------|---|
| 1361     | Remote humidistat control and timer. Fits into a single pattress 20mm deep over run timer |

### P.I.R Model

Passive infra-red model, sensitive to movement will switch the fan on when someone enters the room and off when the room is vacated. The unit also incorporates a time delay switch, which requires no switched live and is energy efficient. Range 5 metres. Fits into a single pattress 20mm deep.

| Cat. No. | Description                  |
|----------|------------------------------|
| 1362     | Remote P.I.R. sensor control |

# Electrical Speed Controllers

## FAN SPEED CONTROLLERS

### Technical Details

Manrose offer a wide range of variable, 2 speed controllers with reversible options. Consult our technical department for full details.

#### Fan Speed Controllers - Non Reversible

The variable non-reversing fan speed control is suitable for controlling the speed of fans providing that the electrical load is not less than 20 Watts or more than 200 Watts. Fits single pattress 20mm deep. A two speed non reversing controller is also available.

| Cat. No. | Description                   |
|----------|-------------------------------|
| 1350     | Variable fan speed controller |
| COMTSCV  | Variable fan speed controller |

#### Fan Speed Controllers - Reversible

Suitable for WF/XF230/300/COMT/TK/CW/G (except MP models) range. Twin speed and variable speed options available.

| Cat. No. | Description   |
|----------|---|
| 1349     | Reversible speed controller (variable)                        |
| COMTSCVR | Reversible speed controller (variable)                        |
| 1348     | Two speed reversible controller (230mm 9" and 300mm 12" fans) |



1350



COMTSCV



1349



COMTSCVR



1348