Extract-A-Lite 12 Volt DC For Caravans, Motor homes, Boats and Marine installations Specialist Range

BSL112/124



A compact combined extractor fan with an integral halogen light. Designed for installation in galleys, showers and toilets, ideal for marine and other leisure applications.

- · Long life computer motor which will run continuously, only 2.8 Watts.
- 12 Volt DC motor, 24 Volt DC motor also available.
- · Ignition protected.
- 50,000 hours operating life expectancy.
- The fan and light may be switched on together or used independently.
- · Easy to install and maintain.
- Quiet and efficient, the Extract-A-Lite has an extraction rate of 64m³/hr or 18 litres per second and only 43 dB(A).
- Designed for Wall/Ceiling or Panel Mounting, terminating through standard UFO or similar deck waterproof fittings.





Technical Details

Cat. No.	Product type
BSF112W	Fan only 12V model - White
BSF124W	Fan only 24V model - White

Dimensions (mm)

PRODUCT	А
BSF112	140Ø
BSF124	140Ø





С

В

D


Е

98

98

Performance Graph

64m3/hr, 18 litres per second



Typical Installation into a boat bathroom



Packaging

In outers of 10 measuring 370mm x 200mm x 560mm - weight 4 kgs.

Installation

Designed for wall, ceiling or panel mounting through 100mm (4") diameter flexible or rigid pipes or low flat channel ducting systems.

Electrical

F

38

38

12V Showerlite, DC 12V 2.8 Watts fan, max airflow 18 litres/sec and max 10 Watts light, G4 lamp.

24V Showerlite, DC 24V 2.8 Watts fan, max airflow 18 litres/sec and max 10 Watts light, G4 lamp.

Additional Data

100mm (4") Range Maximum pressure: 20 p.a. Fan speed: 2400 r.p.m. Sound volume: 43.0 dB(A) Maximum operating temperature: 40°C

