

Flat Fan Range

Domestic Range

FLAT100S/FLAT150S



100mm and 150mm panel axial fans for bathrooms, cloakrooms and kitchens. Slim profile only 15mm. Suitable for wall or panel mounting using the appropriate fixing kit.

- Provides required performance of 54m³/h (15l/s) - bathrooms and 216m³/h (60l/s) - kitchens to comply with the Building Regulations (Document F).
- Panel or Wall mounting.
- Model options with timer control.
- Integral backdraught shutters.



Technical Details

Cat. No. Product type

Bathroom & Toilet Fans

FLAT100S Single speed axial fan with integral backdraught shutters for remote or light switch operation

FLAT100T Single speed axial fan with electronic over-run timer – up to 30 mins and integral backdraught shutters

FLAT100H Humidity version


Kitchen & Utility Room Fans

FLAT150S Single speed axial fan with integral backdraught shutters for remote or light switch operation

FLAT150T Timer version


Dimensions (mm)

PRODUCT	A	BØ	C	D
FLAT100S	159	98	70	15
FLAT100T	159	98	70	15
FLAT100H	159	98	70	15
FLAT150S	225	144	93	15
FLAT150T	225	144	93	15



Performance Graph

Flat100 - 95m³/hr 26l/s



Packaging

Flat Fan series packed in outers of 10. Contact our technical department for packaging dimensions

Electrical

220-240V - AC. 50Hz . Single phase consuming 14 Watts on the 100 series and 16 Watts on the 150 series. These fans are double insulated and do not require an earth. All wiring must comply with current IEE regulations. A double pole isolating switch, having a contact separation of at least 3mm in all poles, must be used with a 3 amp fuse fitted. The fan must not be accessible to a person using either the shower or bath and mounted a minimum of 1.8 metres from the floor.

Additional Data

100mm (4") Range

Maximum pressure: 20 p.a.
Sound volume: 38.0 dB(A)
Maximum operating temperature: 40°C

150mm (6") Range

Maximum pressure: 50 p.a.
Sound volume: 45.0 dB(A)
Maximum operating temperature: 40°C