

Name:	Manrose	Manrose	Manrose	Manrose
Model ID (Stock Ref.) :	MG150BS	MG150BP	MG150ABS	MG150ABP
SEC Class	F	F	F	F
SEC Value ('Average')	-8.63	-8.63	-8.63	-8.63
SEC Value ('Warm')	-0.98	-0.98	-0.98	-0.98
SEC Value ('Cold')	-21.98	-21.98	-21.98	-21.98
Label Required? (Yes/No=Out of scope)	No	No	No	No
Declared as: RVU or NRUVU/UVU or BVU	RVU-UVU	RVU-UVU	RVU-UVU	RVU-UVU
Speed Drive	Variable Speed	Variable Speed	Variable Speed	Variable Speed
Type HRS (Re recuperative, Regenerative, None)	None	None	None	None
Thermal Eff. : (%), NA(if none)	N/A	N/A	N/A	N/A
Max. Flow Rate (m ³ /h)	230.40	230.40	230.40	230.40
Max. Power Input (W): (@Max.Flow Rate)	25.00	25.00	25.00	25.00
LWA: Sound Power Level (dB)	60.53	60.53	60.53	60.53
Ref. Flow Rate (m ³ /s)	0.04	0.04	0.04	0.04
Ref. Pressure Diff. (Pa)	TBC	TBC	TBC	TBC
SPL IW/(m ³ /h)	0.16	0.16	0.16	0.16
Control Factor & Control Typology: (CTRL/ Typology)				
Control Factor: CTRL	1.00	1.00	1.00	1.00
Control Typology	Manual Control	Manual Control	Manual Control	Manual Control
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	TBC	TBC	TBC	TBC
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;	N/A	N/A	N/A	N/A
Filter Warning (RVU)	No	No	No	No
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)	TBC	TBC	TBC	TBC
Internet Address (for Disassembly Instructions)	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Air Tightness-ID/OD-(m ³ /h) (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Annual Electricity Consumption: AEC (kWh/a)	5.34	5.34	5.34	5.34
Annual Heating Saved: AHS (kWh/a)				
AHS: Average	13.97	13.97	13.97	13.97
AHS: Warm	6.32	6.32	6.32	6.32
AHS: Cold	27.32	27.32	27.32	27.32

Manrose	Manrose	Manrose	Manrose	Manrose	Manrose
MG150BT	MG150BTP	MG150ABT	MG150ABTP	MG150BH	MG150BHP
E	E	E	E	C	C
-10.90	-10.90	-10.90	-10.90	-23.97	-23.97
-2.29	-2.29	-2.29	-2.29	-9.60	-9.60
-25.93	-25.93	-25.93	-25.93	-49.06	-49.06
No	No	No	No	No	No
RVU-LUVU	RVU-LUVU	RVU-LUVU	RVU-LUVU	RVU-LUVU	RVU-LUVU
Variable Speed	Variable Speed	Variable Speed	Variable Speed	Variable Speed	Variable Speed
None	None	None	None	None	None
N/A	N/A	N/A	N/A	N/A	N/A
230.40	230.40	230.40	230.40	230.40	230.40
25.00	25.00	25.00	25.00	25.00	25.00
60.53	60.53	60.53	60.53	60.53	60.53
0.04	0.04	0.04	0.04	0.04	0.04
TBC	TBC	TBC	TBC	TBC	TBC
0.16	0.16	0.16	0.16	0.16	0.16
0.95	0.95	0.95	0.95	0.65	0.65
Clock Control	Clock Control	Clock Control	Clock Control	Local Demand Control	Local Demand Control
TBC	TBC	TBC	TBC	TBC	TBC
N/A	N/A	N/A	N/A	N/A	N/A
No	No	No	No	No	No
TBC	TBC	TBC	TBC	TBC	TBC
www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
TBC	TBC	TBC	TBC	TBC	TBC
TBC	TBC	TBC	TBC	TBC	TBC
4.82	4.82	4.82	4.82	2.26	2.26
15.72	15.72	15.72	15.72	26.23	26.23
7.11	7.11	7.11	7.11	11.86	11.86
30.75	30.75	30.75	30.75	51.31	51.31

Manrose	Manrose	Manrose	Manrose
MG150ABH	MG150ABHP	MG150BPIR	MG150ABPIR
C	C	C	C
-23.97	-23.97	-23.97	-23.97
-9.60	-9.60	-9.60	-9.60
-49.06	-49.06	-49.06	-49.06
No	No	No	No
RVU-UVU	RVU-UVU	RVU-UVU	RVU-UVU
Variable Speed	Variable Speed	Variable Speed	Variable Speed
None	None	None	None
N/A	N/A	N/A	N/A
230.40	230.40	230.40	230.40
25.00	25.00	25.00	25.00
60.53	60.53	60.53	60.53
0.04	0.04	0.04	0.04
TBC	TBC	TBC	TBC
0.16	0.16	0.16	0.16
0.65	0.65	0.65	0.65
Local Demand Control	Local Demand Control	Local Demand Control	Local Demand Control
TBC	TBC	TBC	TBC
N/A	N/A	N/A	N/A
No	No	No	No
TBC	TBC	TBC	TBC
www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
TBC	TBC	TBC	TBC
TBC	TBC	TBC	TBC
2.26	2.26	2.26	2.26
26.23	26.23	26.23	26.23
11.86	11.86	11.86	11.86
51.31	51.31	51.31	51.31