

Name:	Manrose	Manrose	Manrose
Model ID (Stock Ref.) :	SELVLW100S	SELVLW100T	SELVLW100H
SEC Class	E	E	C
SEC Value ('Average')	-11.17	-13.19	-25.05
SEC Value ('Warm')	-3.52	-4.58	-10.68
SEC Value ('Cold')	-24.52	-28.22	-50.13
Label Required? (Yes/No=Out of scope)	No	No	No
Declared as: RVU or NRVU/UVU or BVU	RVU-UVU	RVU-UVU	RVU-UVU
Speed Drive	Variable Speed	Variable Speed	Variable Speed
Type HRS (Re recuperative, Regenerative, None)	None	None	None
Thermal Eff. : (%), NA(if none)	N/A	N/A	N/A
Max. Flow Rate (m3/h)	75.60	75.60	75.60
Max. Power Input (W) : (@Max.Flow Rate)	4.30	4.30	4.30
LWA: Sound Power Level (dB)	58.53	58.53	58.53
Ref. Flow Rate (m3/s)	0.01	0.01	0.01
Ref. Pressure Diff. (Pa)	TBC	TBC	TBC
SPL [W]/(m3/h)	0.08	0.08	0.08
Control Factor & Control Typology: (CTRL/ Typology)			
Control Factor: CTRL	1.00	0.95	0.65
Control Typology	Manual Control	Clock Control	Local Demand Control
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	TBC	TBC	TBC
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;	N/A	N/A	N/A
Filter Warning (RVU)	No	No	No
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)	TBC	TBC	TBC
Internet Address (for Disassembly Instructions)	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted Vus)	TBC	TBC	TBC
Air Tightness-ID/OD-(m3/h) (for Non-Ducted Vus)	TBC	TBC	TBC
Annual Electricity Consumption: AEC (kWh/a)	2.80	2.53	1.18
Annual Heating Saved: AHS (kWh/a)			
AHS: Average	13.97	15.72	26.23
AHS: Warm	6.32	7.11	11.86
AHS: Cold	27.32	30.75	51.31