

Name:	Manrose
Model ID (Stock Ref.) :	MAN 100M
Declared as: RVU or NRVU/UVU or BVU	RVU
Speed Drive	Multi/Var.Sp
Type HRS (Recuperative, Regenerative, None)	None
Thermal Eff: [ (%), NA(if none)]	N/A
Nominal Flow Rate (m3/s)	0.04
Effective Elec. Power Input (kW): (@Nom.Flow Rate&Ext. Pressure)	0.09
SFPint [W/(m3/s)]	N/A
Face Velocity (m/s) @ Design Flow Rate	TBC
Nominal External Pressure: ( $\Delta p_{s, ext}$ ) in Pa	50
Internal Pressure Drop of Ventilation Components ( $\Delta p_{s, int}$ ) in Pa;	N/A
Additional Internal Press. Drop of Non-Ventilation Comp.: $\Delta p_{s, add}$ (Pa)	TBC
Static Eff. of fans used in accordance with Regulation (EU) No 327/2011;	TBC
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	N/A
Energy Performance, preferably energy classification, of the Filters (declared information about the calculated AEC)	TBC
Filter Warning (RVU)	TBC
For UVUs (Instructions Install Grilles Façade)	In F&W
Internet Address (for Disassembly Instructions)	<a href="http://www.manrose.co.uk">www.manrose.co.uk</a>

Manrose	Manrose	Manrose	Manrose
MAN 125M	MAN 150M	MAN 200M	MAN 250M
RVU	NRVU	NRVU	NRVU
Multi/Var.Sp	Multi/Var.Sp	Multi/Var.Sp	Multi/Var.Sp
None	None	None	None
N/A	N/A	N/A	N/A
0.04	0.08	0.14	0.14
0.21	0.03	0.03	0.07
N/A	N/A	N/A	N/A
TBC	TBC	TBC	TBC
110	125	150	250
N/A	N/A	N/A	N/A
TBC	TBC	TBC	TBC
TBC	TBC	TBC	TBC
N/A	N/A	N/A	N/A
TBC	TBC	TBC	TBC
TBC	TBC	TBC	TBC
In F&W	In F&W	In F&W	In F&W
<a href="http://www.manrose.co.uk">www.manrose.co.uk</a>	<a href="http://www.manrose.co.uk">www.manrose.co.uk</a>	<a href="http://www.manrose.co.uk">www.manrose.co.uk</a>	<a href="http://www.manrose.co.uk">www.manrose.co.uk</a>