

Name:	Manrose
Model ID (Stock Ref.) :	MANI3000
SEC Class	E
SEC Value ('Average')	-11.96
SEC Value ('Warm')	0.05
SEC Value ('Cold')	-32.93
Label Required? (Yes/No=Out of scope)	Yes
Declared as: RVU or NRVU/UVU or BVU	RVU
Speed Drive	Multi-Speed
Type HRS (Regenerative, Regenerative, None)	None
Thermal Eff. : (%), NA(if none)	N/A
Max. Flow Rate (m3/h)	151.20
Max. Power Input (W) : (@Max.Flow Rate)	43.00
LWA: Sound Power Level (dB)	N/A - (Ducted)
Ref. Flow Rate (m3/s)	0.03
Ref. Pressure Diff. (Pa)	TBC
SPL [W]/(m3/h)	0.41
Control Factor & Control Typology: (CTRL/ Typology)	
Control Factor: CTRL	0.85
Control Typology	Central Demand
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	TBC
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;	TBC
Filter Warning (RVU)	TBC
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)	N/A
Internet Address (for Disassembly Instructions)	www.manrose.co.uk
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted Vus)	N/A
Air Tightness-ID/DD-(m3/h) (for Non-Ducted Vus)	N/A
Annual Electricity Consumption: AEC (kWh/a)	3.99
Annual Heating Saved: AHS (kWh/a)	
AHS: Average	21.93
AHS: Warm	9.92
AHS: Cold	42.90