

Name:	Manrose	Manrose	Manrose	Manrose
Model ID (Stock Ref.) :	SLKSC	SLKTC	SL-1205C	SL-120TC
SEC Class	F	F	F	E
SEC Value ('Average')	-5.05	-7.67	-8.08	-10.41
SEC Value ('Warm')	2.60	0.94	-0.43	-1.80
SEC Value ('Cold')	-18.41	-22.70	-21.44	-25.44
Label Required? (Yes/No=Out of scope)	No	No	No	No
Declared as: RVU or NRUVU/UVU or BVU	RVU-UVU	RVU-UVU	RVU-UVU	RVU-UVU
Speed Drive	Variable Speed	Variable Speed	Variable Speed	Variable Speed
Type HRS (Regenerative, Regenerative, None)	None	None	None	None
Thermal Eff. : (%), NA(if none)	N/A	N/A	N/A	N/A
Max. Flow Rate (m3/h)	82.80	82.80	129.60	129.60
Max. Power Input (W): (@Max.Flow Rate)	15.00	15.00	15.50	15.50
LWA: Sound Power Level (dB)	61.53	61.53	61.53	61.53
Ref. Flow Rate (m3/s)	0.02	0.02	0.03	0.03
Ref. Pressure Diff. (Pa)	TBC	TBC	TBC	TBC
SPL [W/(m3/h)]	0.26	0.26	0.17	0.17
Control Factor & Control Typology: (CTRL/ Typology)				
Control Factor: CTRL	1.00	0.95	1.00	0.95
Control Typology	Manual Control	Clock Control	Manual Control	Clock Control
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;	TBC	TBC	TBC	TBC
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;	N/A	N/A	N/A	N/A
Filter Warning (RVU)	No	No	No	No
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)	TBC	TBC	TBC	TBC
Internet Address (for Disassembly Instructions)	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Air Tightness-ID/OD-(m3/h) (for Non-Ducted Vus)	TBC	TBC	TBC	TBC
Annual Electricity Consumption: AEC (kWh/a)	8.92	8.05	5.89	5.31
Annual Heating Saved: AHS (kWh/a)				
AHS: Average	13.97	15.72	13.97	15.72
AHS: Warm	6.32	7.11	6.32	7.11
AHS: Cold	27.32	30.75	27.32	30.75

Manrose	Manrose	Manrose	Manrose
SL-150SC	SL-150TC	SLCFDSC	SLCFDTC
F	E	F	F
-8.63	-10.90	-5.15	-7.76
-0.98	-2.29	2.50	0.85
-21.98	-25.93	-18.50	-22.79
No	No	No	No
RVU-UVU	RVU-UVU	RVU-UVU	RVU-UVU
Variable Speed	Variable Speed	Variable Speed	Variable Speed
None	None	None	None
N/A	N/A	N/A	N/A
230.40	230.40	111.60	111.60
25.00	25.00	20.00	20.00
60.53	60.53	65.53	65.53
0.04	0.04	0.02	0.02
TBC	TBC	TBC	TBC
0.16	0.16	0.26	0.26
1.00	0.95	1.00	0.95
Manual Control	Clock Control	Manual Control	Clock Control
TBC	TBC	TBC	TBC
N/A	N/A	N/A	N/A
No	No	No	No
TBC	TBC	TBC	TBC
www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk	www.manrose.co.uk
TBC	TBC	TBC	TBC
TBC	TBC	TBC	TBC
5.34	4.82	8.82	7.96
13.97	15.72	13.97	15.72
6.32	7.11	6.32	7.11
27.32	30.75	27.32	30.75